

This form is a summary description of the model entitled “Parking” proposed for the Model Checking Contest @ Petri Nets. Models can be given in several instances parameterized by scaling parameters. Colored nets can be accompanied by one or many equivalent, unfolded P/T nets. Models are given together with property files (possibly, one per model instance) giving a set of properties to be checked on the model.

Description

This collection of P/T nets was derived from the formal specification of a car parking control system. The parking lot is divided into several areas. The accesses to each area are controlled by a set of PLCs (*Programmable Logic Controllers*), which monitor the availability in real-time, and direct cars entering the parking to the area with the highest availability if the requested area is fully occupied. For each area, there is one *master* PLC that supervises several so-called *slave* PLCs. The PLCs communicate via a MODBUS network and the whole system can be considered as a GALS (*Globally Asynchronous, Locally Synchronous*) system.

The parking system was formally described in GRL, a specification language dedicated to PLCs and GALS. Each GRL specification was automatically translated to LNT (*LOTOS New Technology*), then to LOTOS, and then to an interpreted Petri net using the [CADP](#) toolbox. Finally, a P/T net was obtained by stripping out all dataflow-related information (variables, types, assignments, guards, etc.) from the interpreted Petri net, leading to a NUPN (*Nested-Unit Petri Net*) model translated to PNML using the [CÆSAR.BDD](#) tool.

References

Fatma Jebali, Frédéric Lang, and Radu Mateescu. *GRL: A Specification Language for Globally Asynchronous Locally Synchronous Systems*. Proceedings of the 16th International Conference on Formal Engineering Methods (ICFEM’2014), Luxembourg, November 3-5, 2014. LNCS 8829, Springer.

Scaling parameter

Parameter name	Parameter description	Chosen parameter values
(M, S)	M : number of master PLCs, S : number of slave PLCs	(1, 4), (2, 8), (4, 16), (8, 32), (4, 32), (8, 64)

Size of the model

Parameter	Number of places	Number of transitions	Number of arcs
(1, 4)	65	97	284
(2, 8)	137	201	593
(4, 16)	305	433	1289
(8, 32)	737	993	2993
(4, 32)	529	785	2329
(8, 64)	1185	1697	5073

Structural properties

- ordinary — all arcs have multiplicity one ✓
- simple free choice — all (different) transitions with a shared input place have no other input place ✗ (a)
- state machine — every transition has exactly one input place and exactly one output place ✗ (b)
- marked graph — every place has exactly one input transition and exactly one output transition ✗ (c)

(a) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
 (b) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
 (c) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.

- connected** — *there is an undirected path between every two nodes (places or transitions)* ✓ (d)
- strongly connected** — *there is a directed path between every two nodes (places or transitions)* ✗ (e)
- source place(s)** — *one or more places have no input transitions* ✓ (f)
- sink place(s)** — *one or more places have no output transitions* ✗ (g)
- source transition(s)** — *one or more transitions have no input places* ✗ (h)
- sink transitions(s)** — *one or more transitions have no output places* ✗ (i)
- loop-free** — *no transition has an input place that is also an output place* ✗ (j)
- conservative** — *for each transition, the number of input arcs equals the number of output arcs* ✗ (k)
- subconservative** — *for each transition, the number of input arcs equals or exceeds the number of output arcs* ✗ (l)
- nested units** — *places are structured into hierarchically nested sequential units*^(m) ✓ (n)

Behavioural properties

- safe** — *in every reachable marking, there is no more than one token on a place* ✓ (o)
- deadlock** — *there exists a reachable marking from which no transition can be fired* ✓ (p)
- reversible** — *from every reachable marking, there is a transition path going back to the initial marking* ✗ (q)
- quasi-live** — *for every transition t , there exists a reachable marking in which t can fire* ✓ (r)
- live** — *for every transition t , from every reachable marking, one can reach a marking in which t can fire* ✗ (s)

Size of the marking graphs

Parameter	Number of reachable markings	Number of transition firings	Max. number of tokens per place	Max. number of tokens per marking
(1, 4)	31745 ^(t)	?	1 ^(u)	15 ^(v)
(2, 8)	4.5676E+09 ^(w)	?	1 ^(x)	32 ^(y)
(4, 16)	8.44047E+21 ^(z)	?	1 ^(aa)	72 ^(ab)
(8, 32)	$\geq 5.71544E+44$ ^(ac)	?	1 ^(ad)	176 ^(ae)
(4, 32)	3.67025E+32 ^(af)	?	1 ^(ag)	120 ^(ah)
(8, 64)	$\geq 6.2771E+65$ ^(ai)	?	1 ^(aj)	272 ^(ak)

- (d) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (e) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (f) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (g) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (h) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (i) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (j) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (k) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (l) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (m) the definition of Nested-Unit Petri Nets (NUPN) is available from <http://mcc.lip6.fr/nupn.php>
- (n) stated by [CÆSAR.BDD](#) version 2.2 on all the 6 instances.
- (o) safe by construction – stated by the [CÆSAR](#) compiler on all the 6 instances.
- (p) stated by [CÆSAR.BDD](#) version 2.2 to be true on 4 instances out of 6, and unknown on the remaining 2 instances.
- (q) stated by [CÆSAR.BDD](#) version 2.2 to be false on 4 instances out of 6, and unknown on the remaining 2 instances.
- (r) stated by [CÆSAR.BDD](#) version 2.2 to be true on 4 instances out of 6, and unknown on the remaining 2 instances.
- (s) stated by [CÆSAR.BDD](#) version 2.2 to be false on 4 instances out of 6, and unknown on the remaining 2 instances.
- (t) stated by [CÆSAR.BDD](#) version 2.2.
- (u) stated by the [CÆSAR](#) compiler.
- (v) stated by [CÆSAR.BDD](#) version 2.2.
- (w) stated by [CÆSAR.BDD](#) version 2.2.
- (x) stated by the [CÆSAR](#) compiler.
- (y) stated by [CÆSAR.BDD](#) version 2.2.
- (z) stated by [CÆSAR.BDD](#) version 2.2.
- (aa) stated by the [CÆSAR](#) compiler.
- (ab) stated by [CÆSAR.BDD](#) version 2.2.
- (ac) stated by [CÆSAR.BDD](#) version 2.2.
- (ad) stated by the [CÆSAR](#) compiler.
- (ae) stated by [CÆSAR.BDD](#) version 2.2.

(af) stated by [CÆSAR.BDD](#) version 2.2.
(ag) stated by the [CÆSAR](#) compiler.
(ah) stated by [CÆSAR.BDD](#) version 2.2.
(ai) stated by [CÆSAR.BDD](#) version 2.2.
(aj) stated by the [CÆSAR](#) compiler.
(ak) stated by [CÆSAR.BDD](#) version 2.2.