
This form is a summary description of the model entitled "Permutation admissibility in multistage interconnection networks" proposed for the Model Checking Contest @ Petri Nets. Models can be given in several instances parameterized by scaling parameters. Colored nets can be accompanied by one or many equivalent, unfolded P/T nets. Models are given together with property files (possibly, one per model instance) giving a set of properties to be checked on the model.

# Description

The model describes a  $8 \times 8$  4 stages shuffle-exchange network. In order to ease readability, the net components are grouped in columns similar to the way the switches are arranged in stages. Thus, whole net is represented as a cascade of columns alternating in type of the components being either place or transition. Transitions occur column-wise from the leftmost to the rightmost and in columns from the topmost to the bottommost. It can be easily seen that no token can visit a place more than once. Direction of the arcs indicates the flow of tokens through the net.

Here, we consider the scaling parameter N as a multiplier for the initial marking in places  $\mathbf{in}\langle x\rangle$  and **c5**. The figure shows the model when N=1.



Graphical representation for N=1

#### References

R. Bashirov, F. Kordon, and H. Lort. Exploiting colored Petri nets to decide on permutation admissibility. *Acta Informatica*, 46(1):43–55, February 2009.

# Scaling parameter

Parameter name	Parameter description	Chosen parameter values	
N	Multiplier for the marking of places $\mathbf{in}\langle x\rangle$	1, 2, 5, 10, 20, 50	
	and <b>c5</b>		

### Size of the model

Although the model is parameterized, its size does not depend on parameter values.

number of places: 40 number of transitions: 16 number of arcs: 83

### Structural properties

ordinary — all arcs have multiplicity one	<b>X</b>
simple free choice — all transitions sharing a common input place have no other input place	<b>X</b> (a)
	<b>X</b> (b)
	<b>X</b> (c)
	<b>X</b> (d)
connected — there is an undirected path between every two nodes (places or transitions)	<b>✓</b> (e)
strongly connected — there is a directed path between every two nodes (places or transitions)	<b>X</b> (f)
	<b>√</b> (g)
	<b>√</b> (h)
	<b>X</b> (i)
sink transitions(s) — one or more transitions have no output places	<b>X</b> (j)
loop-free — no transition has an input place that is also an output place	<b>√</b> (k)
conservative — for each transition, the number of input arcs equals the number of output arcs	<b>X</b> (1)
subconservative — for each transition, the number of input arcs equals or exceeds the number of output arcs	<b>X</b> (m)
nested units — places are structured into hierarchically nested sequential units (n)	<b>X</b>

# Behavioural properties

safe — in every reachable marking, there is no more than one token on a place
deadlock — there exists a reachable marking from which no transition can be fired
reversible — from every reachable marking, there is a transition path going back to the initial marking
quasi-live — for every transition t, there exists a reachable marking in which t can fire?
live — for every transition t, from every reachable marking, one can reach a marking in which t can fire?

<sup>(</sup>a) the net is not ordinary in all its 6 instances (1, 2, 5, 10, 20, and 50).

<sup>(</sup>b) the net is not ordinary in all its 6 instances (1, 2, 5, 10, 20, and 50).

 $<sup>^{(</sup>c)}$  the net is not ordinary in all its 6 instances (1, 2, 5, 10, 20, and 50).

 $<sup>^{(</sup>d)}$  the net is not ordinary in all its 6 instances (1, 2, 5, 10, 20, and 50).

 $<sup>^{(</sup>e)}$  stated by CÆSAR.BDD version 1.7 on all 6 instances (1, 2, 5, 10, 20, and 50).

 $<sup>^{(</sup>f)}$  from place "aux16\_0" one cannot reach place "in4\_6".

<sup>(</sup>g) there exist 9 source places, e.g., place "in4\_6".

<sup>(</sup>h) there exist 64 sink places, e.g., place "out7\_1".

<sup>(</sup>i) stated by CÆSAR.BDD version 1.7 on all 6 instances (1, 2, 5, 10, 20, and 50).

<sup>(</sup>j) stated by CÆSAR.BDD version 1.7 on all 6 instances (1, 2, 5, 10, 20, and 50).

<sup>(</sup>k) stated by CÆSAR.BDD version 1.7 on all 6 instances (1, 2, 5, 10, 20, and 50).

<sup>(</sup>l) stated by PNML2NUPN 1.3.0 on all 6 instances (1, 2, 5, 10, 20, and 50). (m) stated by PNML2NUPN 1.3.0 on all 6 instances (1, 2, 5, 10, 20, and 50).

<sup>(</sup>n) the definition of Nested-Unit Petri Nets (NUPN) is available from http://mcc.lip6.fr/nupn.php

<sup>(</sup>o) in the initial marking, some places have several tokens (the number of which depends on N).

<sup>(</sup>P) confirmed at MCC'2014 by Helena on all 6 colored instances, and by Lola and Tapaal on all 6 P/T instances.

# Size of the marking graphs

Parameter	Number of reach-	Number of tran-	Max. number of	Max. number of
	able markings	sition firings	tokens per place	tokens per marking
N = 1	52 537 <sup>(q)</sup>	54 600 <sup>(r)</sup>	1 <sup>(s)</sup>	9 (t)
N=2	?	?	?	≥ 18
N=5	?	?	?	$\geq 45$
N = 10	?	?	?	$\geq 90$
N = 20	?	?	?	≥ 180
N = 50	?	?	?	$\geq 450$

 $<sup>^{(</sup>q)}$  Computed by Alpina, and ITS-Tools at MCC'2013; confirmed at MCC'2014 by Helena on the colored net instance, and by GreatSPN, Marcie, PNMC, PNXDD, and Tapaal on the P/T net instance.

 $<sup>^{(</sup>r)}$  computed at MCC'2014 by Helena on the colored net instance, and by Marcie on the P/T net instance.

 $<sup>^{(</sup>s)}$  computed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal on the P/T net instance.

<sup>(</sup>t) computed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal on the P/T net instance.