

This form is a summary description of the model entitled “Resource Allocation Model” proposed for the Model Checking Contest @ Petri Nets. Models can be given in several instances parameterized by scaling parameters. Colored nets can be accompanied by one or many equivalent, unfolded P/T nets. Models are given together with property files (possibly, one per model instance) giving a set of properties to be checked on the model.

Description

Let us consider a kind of chessboard, whose dimensions are nR ($nR \geq 1$) and nC ($nC \geq 2$), respectively, in which each position has a given capacity (let say $K \geq 1$) for holding ants. Let us also consider ant processes which traverse the board, either North-South or South-North directions, always jumping from one position to the following one. For safety reasons each ant, before jumping to the next position, books the position he is going to jump over and also the adjacent one in the west side of the target position. Of course, because of the position capacity constraint, no more than K ants can stay simultaneously in the same position.


In the set of considered specific models, even columns correspond to North-South ant processes, while odd columns correspond to South-North ant processes. The figure sketches a particular board model for $nR=3$, $nC=5$ and $K=1$.

The system can be parametrized in three ways, varying each one of nR , nC and K (here $K=1$). When varying nR we will call the model a RAS-R, and when varying nC we will call it a RAS-C.

These models belong the family of Resource Allocation Systems, RAS. A RAS is composed of a finite set of processes that share in a competitive way a finite set of resources. In a system there can be resources of several types, and for each type there can be several available copies. In this case, the model belong to the family of the S^4PR nets, as described in [TrEz2006].

Places p_* correspond to *state places*, while places r_* correspond to *resource places*. Resource places model the state of the resources shared by the ant processes (in this case the state of a resource is identified as its free capacity). State places model the board position where an ant process is at a given moment.

In March 2020, Pierre Bouvier and Hubert Garavel provided a decomposition of all instances of this model into networks of communicating automata. Each network is expressed as a Nested-Unit Petri Net (NUPN) that can be found, for each instance, in the “toolspecific” section of the corresponding PNML file.



References

Tricas, F.; Ezpeleta, J. *Computing minimal siphons in Petri net models of resource allocation systems: a parallel solution*. IEEE Transactions on Systems, Man and Cybernetics. Part A, Volume 36, Issue 3, Pages 532–539. May 2006.

The program used to generate the PNML models can be downloaded from:

https://github.com/fernand0/Petri-Net-tools/blob/master/model_generator.c

There is a script to generate all the models for a selected set of parameters, at:

<https://github.com/fernand0/Petri-Net-tools/blob/master/pnml.sh>.

Scaling parameter

Parameter name	Parameter description	Chosen parameter values
(nR, nC)	Number of (rows, columns)	(2,2), (3,2), (3,3), (3,5), (3,10), (3,15), (3,20), (3,50), (3,100), (5,2), (10,2), (15,2), (20,2), (50,2), (100,2)

Size of the model

Parameter	Number of places	Number of transitions	Number of arcs	Number of units	HWB code
(nR, nC)	$2 \cdot nR \cdot nC$	$nC \cdot (nR + 1)$	$4 \cdot nR \cdot nC + 2 \cdot nR \cdot (nC - 1)$?	1-?-?
$(nR, nC) = 2, 2$	8	6	20	5	1-4-6
$(nR, nC) = 3, 2$	12	8	30	7	1-6-9
$(nR, nC) = 3, 3$	18	12	48	10	1-9-12
$(nR, nC) = 3, 5$	30	20	84	16	1-15-23
$(nR, nC) = 3, 10$	60	40	174	31	1-30-45
$(nR, nC) = 3, 15$	90	60	264	46	1-45-69
$(nR, nC) = 3, 20$	120	80	354	61	1-60-90
$(nR, nC) = 3, 50$	300	200	894	151	1-150-225
$(nR, nC) = 3, 100$	600	400	1794	301	1-300-450
$(nR, nC) = 5, 2$	20	12	50	11	1-10-15
$(nR, nC) = 10, 2$	40	22	100	21	1-20-30
$(nR, nC) = 15, 2$	60	32	150	31	1-30-45
$(nR, nC) = 20, 2$	80	42	200	41	1-40-60
$(nR, nC) = 50, 2$	200	102	500	101	1-100-150
$(nR, nC) = 100, 2$	400	202	1000	201	1-200-300

Structural properties

ordinary — all arcs have multiplicity one	✓
simple free choice — all transitions sharing a common input place have no other input place	✗ (a)
extended free choice — all transitions sharing a common input place have the same input places	✗ (b)
state machine — every transition has exactly one input place and exactly one output place	✗ (c)
marked graph — every place has exactly one input transition and exactly one output transition	✗ (d)
connected — there is an undirected path between every two nodes (places or transitions)	✓ (e)
strongly connected — there is a directed path between every two nodes (places or transitions)	✓ (f)
source place(s) — one or more places have no input transitions	✗ (g)
sink place(s) — one or more places have no output transitions	✗ (h)
source transition(s) — one or more transitions have no input places	✗ (i)
sink transitions(s) — one or more transitions have no output places	✗ (j)
loop-free — no transition has an input place that is also an output place	✓ (k)
conservative — for each transition, the number of input arcs equals the number of output arcs	✗ (l)
subconservative — for each transition, the number of input arcs equals or exceeds the number of output arcs	✗ (m)
nested units — places are structured into hierarchically nested sequential units ⁽ⁿ⁾	✓

(a) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(b) stated by CÆSAR.BDD version 2.6 on all 15 instances (see all aforementioned parameter values).

(c) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(d) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(e) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(f) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(g) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(h) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(i) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(j) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(k) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(l) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(m) stated by CÆSAR.BDD version 1.7 on all 15 instances (see all aforementioned parameter values).

(n) the definition of Nested-Unit Petri Nets (NUPN) is available from <http://mcc.lip6.fr/nupn.php>

Behavioural properties

safe — <i>in every reachable marking, there is no more than one token on a place</i>	✓ (o)
dead place(s) — <i>one or more places have no token in any reachable marking</i>	? (p)
dead transition(s) — <i>one or more transitions cannot fire from any reachable marking</i>	✗ (q)
deadlock — <i>there exists a reachable marking from which no transition can be fired</i>	✓ (r)
reversible — <i>from every reachable marking, there is a transition path going back to the initial marking</i>	✗ (s)
live — <i>for every transition t, from every reachable marking, one can reach a marking in which t can fire</i>	✗ (t)

Size of the marking graphs

Parameter	Number of reachable markings	Number of transition firings	Max. number of tokens per place	Max. number of tokens per marking
$(nR, nC) = 2, 2$	8 ^(u)	12 ^(v)	1 ^(w)	4 ^(x)
$(nR, nC) = 3, 2$	20 ^(y)	34 ^(z)	1 ^(aa)	6 ^(ab)
$(nR, nC) = 3, 3$	92 ^(ac)	257 ^(ad)	1 ^(ae)	9 ^(af)
$(nR, nC) = 3, 5$	1200 ^(ag)	4960 ^(ah)	1 ^(ai)	15 ^(aj)
$(nR, nC) = 3, 10$	823 552 ^(ak)	6.2867E+6 ^(al)	1 ^(am)	30 ^(an)
$(nR, nC) = 3, 15$	5.7888E+8 ^(ao)	6.4857E+9 ^(ap)	1 ^(aq)	45 ^(ar)
$(nR, nC) = 3, 20$	4.0646E+11 ^(as)	6.0029E+12 ^(at)	1 ^(au)	60 ^(av)
$(nR, nC) = 3, 50$	4.8718E+28 ^(aw)	1.7616E+30 ^(ax)	1 ^(ay)	150 ^(az)
$(nR, nC) = 3, 100$	1.4195E+57 ^(ba)	1.0194E+59 ^(bb)	1 ^(bc)	300 ^(bd)
$(nR, nC) = 5, 2$	112 ^(be)	240 ^(bf)	1 ^(bg)	10 ^(bh)
$(nR, nC) = 10, 2$	6144 ^(bi)	20 480 ^(bj)	1 ^(bk)	20 ^(bl)
$(nR, nC) = 15, 2$	278 528 ^(bm)	1.2698E+6 ^(bn)	1 ^(bo)	30 ^(bp)
$(nR, nC) = 20, 2$	1.1534E+07 ^(bq)	6.6847E+7 ^(br)	1 ^(bs)	40 ^(bt)
$(nR, nC) = 50, 2$	2.9273E+16 ^(bu)	3.8844E+17 ^(bv)	1 ^(bw)	100 ^(bx)
$(nR, nC) = 100, 2$	6.4650E+31 ^(by)	1.6654E+33 ^(bz)	1 ^(ca)	200 ^(cb)

- (o) stated by [CÆSAR.BDD](#) version 3.3 on all 15 instance(s).
(p) stated by [CÆSAR.BDD](#) version 3.3 to be false on 13 instance(s) out of 15, and unknown on the remaining 2 instance(s).
(q) stated by [CÆSAR.BDD](#) version 2.0 to be false on 13 instance(s) out of 15, and unknown on the remaining 3 instance(s).
(r) stated by [CÆSAR.BDD](#) version 2.0 to be true on 13 instance(s) out of 15, and unknown on the remaining 3 instance(s); confirmed at MCC'2014 by Cunf, Lola, and Tapaal on all instances, and by GreatSPN and PNxDD on fewer instances.
(s) the marking graph has deadlocks and contains more than one reachable marking.
(t) the net has at least one transition and its marking graph has deadlocks.
(u) computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, Stratagem, and Tapaal.
(v) computed at MCC'2014 by Marcie.
(w) confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.
(x) computed at MCC'2014 by Marcie, PNMC, and Tapaal.
(y) computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, Stratagem, and Tapaal.
(z) computed at MCC'2014 by Marcie.
(aa) confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.
(ab) computed at MCC'2014 by Marcie, PNMC, and Tapaal.
(ac) computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, Stratagem, and Tapaal.
(ad) computed at MCC'2014 by Marcie.
(ae) confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.
(af) computed at MCC'2014 by Marcie, PNMC, and Tapaal.
(ag) computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, Stratagem, and Tapaal.
(ah) computed at MCC'2014 by Marcie.
(ai) confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.
(aj) computed at MCC'2014 by Marcie, PNMC, and Tapaal.
(ak) computed at MCC'2013 by ITS-Tools, Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, Stratagem, and Tapaal.
(al) computed at MCC'2014 by Marcie.
(am) confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

Other properties

- For each resource, r_{i-j} , the set $\{r_{i-j}, p_{i-j}, p_{(i+1)-j}\}$ ($\{r_{i-j}, p_{i-j}\}$ for the most eastern process) is the support of a (minimal) 1-valued P-semiflow, stating the conservativeness of the resource capacity. The whole set of that P-semiflow forms a basis of the set of P-semiflows.
- For each ant process j , the set of involved transitions $\{t_{j-0}, t_{j-1}, \dots, t_{j-nR}\}$ is the support of a (minimal) 1-valued T-semiflow, stating the repetitiveness of the process. The whole set of that T-semiflow forms a basis of the set of T-semiflows.

(an) computed at MCC'2014 by Marcie, PNMC, and Tapaal.

(ao) computed at MCC'2013 by ITS-Tools, Marcie, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, and Stratagem.

(ap) computed at MCC'2014 by Marcie.

(aq) confirmed at MCC'2014 by GreatSPN, Marcie, and PNMC.

(ar) computed at MCC'2014 by Marcie and PNMC.

(as) computed at MCC'2013 by ITS-Tools, Marcie, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by Marcie, PNMC, and PNxDD.

(at) computed at MCC'2014 by Marcie.

(au) confirmed at MCC'2014 by Marcie and PNMC.

(av) computed at MCC'2014 by Marcie and PNMC.

(aw) computed at MCC'2013 by ITS-Tools, Marcie, and PNxD; confirmed at MCC'2014 by Marcie, PNMC, and PNxDD.

(ax) computed at MCC'2014 by Marcie.

(ay) computed at MCC'2014 by Marcie and PNMC.

(az) computed at MCC'2014 by Marcie and PNMC.

(ba) computed at MCC'2013 by ITS-Tools, Marcie, and PNxDD; confirmed at MCC'2014 by Marcie, PNMC, and PNxDD.

(bb) computed at MCC'2014 by Marcie.

(bc) computed at MCC'2014 by Marcie and PNMC.

(bd) computed at MCC'2014 by Marcie and PNMC.

(be) computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, Stratagem, and Tapaal.

(bf) computed at MCC'2014 by Marcie.

(bg) confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

(bh) computed at MCC'2014 by Marcie, PNMC, and Tapaal.

(bi) computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, Stratagem, and Tapaal.

(bj) computed at MCC'2014 by Marcie.

(bk) confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

(bl) computed at MCC'2014 by Marcie, PNMC, and Tapaal.

(bm) computed at MCC'2013 by ITS-Tools, Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, Stratagem, and Tapaal.

(bn) computed at MCC'2014 by Marcie.

(bo) confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

(bp) computed at MCC'2014 by Marcie, PNMC, and Tapaal.

(bq) computed at MCC'2013 by Marcie, Neco, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNxDD, and Stratagem.

(br) computed at MCC'2014 by Marcie.

(bs) confirmed at MCC'2014 by GreatSPN, Marcie, and PNMC.

(bt) computed at MCC'2014 by Marcie and PNMC.

(bu) computed at MCC'2013 by Marcie, and PNxDD; confirmed by [CÆSAR.BDD](#) version 1.8; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and PNxDD.

(bv) computed at MCC'2014 by Marcie.

(bw) confirmed at MCC'2014 by GreatSPN, Marcie, and PNMC.

(bx) computed at MCC'2014 by Marcie and PNMC.

(by) computed at MCC'2013 by Marcie, and PNxDD; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, and PNxDD.

(bz) computed at MCC'2014 by Marcie.

(ca) confirmed at MCC'2014 by GreatSPN, Marcie, and PNMC.

(cb) computed at MCC'2014 by Marcie and PNMC.