

This form is a summary description of the model entitled “FunctionPointer” proposed for the Model Checking Contest @ Petri Nets. Models can be given in several instances parameterized by scaling parameters. Colored nets can be accompanied by one or many equivalent, unfolded P/T nets. Models are given together with property files (possibly, one per model instance) giving a set of properties to be checked on the model.

Description

This example is part of a suite that consists of 46 Petri nets that were used in the evaluation of BFC [1]. They originate from the analysis of concurrent C programs.

This example is built from a program using several basic language features and the pthread library.

This model was then used as one of the benchmarks for the tool Petrinizer in [2].

The source model has an initial marking ($l_0 \geq 1$) constraint rather than a single initial marking, this is used in the MCC to scale the model up.

Models found in [3] were converted to PNML thanks to an ITS-Tools [4] library.

References

1. A. Kaiser, D. Kroening, and T. Wahl. Efficient coverability analysis by proof minimization. In CONCUR, volume 7454 of Lecture Notes in Computer Science, pages 500–515. Springer, 2012.
2. J. Esparza, R. Ledesma-Garza, R. Majumdar, P. J. Meyer, and F. Niksic. An smt-based approach to coverability analysis. In CAV, volume 8559 of Lecture Notes in Computer Science, pages 603–619. Springer, 2014
3. Klara J. Meyer, Petrinizer repository, <https://github.com/meyerphi/petrinizer>.
4. Y. Thierry-Mieg, Homepage of ITS-tools <https://lip6.github.io/ITSTools-web/>

Scaling parameter

Parameter name	Parameter description	Chosen parameter values
V, M	V is the variant of the model (A, B or C), and M is the number of tokens in place 10	$\{a, b, c\} \times \{2, 4, 8, 16, 32, 64, 128\}$

Size of the model

Parameter	Number of places	Number of transitions	Number of arcs
Variant a, M=2	40	70	284
Variant a, M=4	40	70	284
Variant a, M=8	40	70	284
Variant a, M=16	40	70	284
Variant a, M=32	40	70	284
Variant a, M=64	40	70	284
Variant a, M=128	40	70	284
Variant b, M=2	306	840	3392
Variant b, M=4	306	840	3392
Variant b, M=8	306	840	3392
Variant b, M=16	306	840	3392
Variant b, M=32	306	840	3392
Variant b, M=64	306	840	3392
Variant b, M=128	306	840	3392
Variant c, M=2	2826	8960	36096
Variant c, M=4	2826	8960	36096
Variant c, M=8	2826	8960	36096
Variant c, M=16	2826	8960	36096
Variant c, M=32	2826	8960	36096
Variant c, M=64	2826	8960	36096
Variant c, M=128	2826	8960	36096

Structural properties

ordinary	— all arcs have multiplicity one yes
simple free choice	— all transitions sharing a common input place have no other input place no ^(a)
extended free choice	— all transitions sharing a common input place have the same input places no ^(b)
state machine	— every transition has exactly one input place and exactly one output place no ^(c)
marked graph	— every place has exactly one input transition and exactly one output transition no ^(d)
connected	— there is an undirected path between every two nodes (places or transitions) no ^(e)
strongly connected	— there is a directed path between every two nodes (places or transitions) no ^(f)
source place(s)	— one or more places have no input transitions yes ^(g)
sink place(s)	— one or more places have no output transitions yes ^(h)
source transition(s)	— one or more transitions have no input places no ⁽ⁱ⁾
sink transitions(s)	— one or more transitions have no output places no ^(j)
loop-free	— no transition has an input place that is also an output place no ^(k)
conservative	— for each transition, the number of input arcs equals the number of output arcs no ^(l)
subconservative	— for each transition, the number of input arcs equals or exceeds the number of output arcs no ^(m)
nested units	— places are structured into hierarchically nested sequential units ⁽ⁿ⁾ no

^(a) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

^(b) transitions “t0” and “t2” share a common input place “s0”, but only the former transition has input place “i0”.

^(c) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

^(d) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

^(e) 2 places are not connected to place “s0”, e.g., place “s6”.

^(f) the net is not connected and, thus, not strongly connected.

^(g) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

^(h) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

⁽ⁱ⁾ stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

^(j) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

^(k) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

^(l) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

^(m) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants × 7 values of M).

⁽ⁿ⁾ the definition of Nested-Unit Petri Nets (NUPN) is available from <http://mcc.lip6.fr/nupn.php>

Behavioural properties

- safe** — *in every reachable marking, there is no more than one token on a place* no ^(o)
dead place(s) — *one or more places have no token in any reachable marking* yes ^(p)
dead transition(s) — *one or more transitions cannot fire from any reachable marking* yes ^(q)
deadlock — *there exists a reachable marking from which no transition can be fired* ?
reversible — *from every reachable marking, there is a transition path going back to the initial marking* ?
live — *for every transition t , from every reachable marking, one can reach a marking in which t can fire* ?

Size of the marking graphs

Parameter	Number of reach-able markings	Number of tran-sition firings	Max. number of tokens per place	Max. number of tokens per marking
Variant a, M=2	?	?	?	≥ 3 ^(r)
Variant a, M=4	?	?	?	≥ 5 ^(s)
Variant a, M=8	?	?	?	≥ 9 ^(t)
Variant a, M=16	?	?	?	≥ 17 ^(u)
Variant a, M=32	?	?	?	≥ 33 ^(v)
Variant a, M=64	?	?	?	≥ 65 ^(w)
Variant a, M=128	?	?	?	≥ 129 ^(x)
Variant b, M=2	?	?	?	≥ 3 ^(y)
Variant b, M=4	?	?	?	≥ 5 ^(z)
Variant b, M=8	?	?	?	≥ 9 ^(aa)
Variant b, M=16	?	?	?	≥ 17 ^(ab)
Variant b, M=32	?	?	?	≥ 33 ^(ac)
Variant b, M=64	?	?	?	≥ 65 ^(ad)
Variant b, M=128	?	?	?	≥ 129 ^(ae)
Variant c, M=2	?	?	?	≥ 3 ^(af)
Variant c, M=4	?	?	?	≥ 5 ^(ag)
Variant c, M=8	?	?	?	≥ 9 ^(ah)
Variant c, M=16	?	?	?	≥ 17 ^(ai)
Variant c, M=32	?	?	?	≥ 33 ^(aj)
Variant c, M=64	?	?	?	≥ 65 ^(ak)
Variant c, M=128	?	?	?	≥ 129 ^(al)

^(o) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants \times 7 values of M).

^(p) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants \times 7 values of M).

^(q) stated by [CÆSAR.BDD](#) version 3.7 on all 21 instances (3 variants \times 7 values of M).

^(r) lower bound given by the number of initial tokens.

^(s) lower bound given by the number of initial tokens.

^(t) lower bound given by the number of initial tokens.

^(u) lower bound given by the number of initial tokens.

^(v) lower bound given by the number of initial tokens.

^(w) lower bound given by the number of initial tokens.

^(x) lower bound given by the number of initial tokens.

^(y) lower bound given by the number of initial tokens.

^(z) lower bound given by the number of initial tokens.

^(aa) lower bound given by the number of initial tokens.

^(ab) lower bound given by the number of initial tokens.

^(ac) lower bound given by the number of initial tokens.

^(ad) lower bound given by the number of initial tokens.

^(ae) lower bound given by the number of initial tokens.

^(af) lower bound given by the number of initial tokens.

^(ag) lower bound given by the number of initial tokens.

^(ah) lower bound given by the number of initial tokens.

^(ai) lower bound given by the number of initial tokens.

^(aj) lower bound given by the number of initial tokens.

^(ak) lower bound given by the number of initial tokens.

^(al) lower bound given by the number of initial tokens.