


This form is a summary description of the model entitled “HirschbergSinclair” proposed for the Model Checking Contest @ Petri Nets. Models can be given in several instances parameterized by scaling parameters. Colored nets can be accompanied by one or many equivalent, unfolded P/T nets. Models are given together with property files (possibly, one per model instance) giving a set of properties to be checked on the model.

Description

This Petri net models a simplified version of the Hirschberg and Sinclair algorithm (leader election in a synchronous ring network). This was one of the Tra My Nguyen’s exercices during her bachelor.



Graphical representation for $n = 2$

References

Daniel S. Hirschberg, James B. Sinclair: Decentralized Extrema-Finding in Circular Configurations of Processors. Communications of the ACM 23(11): 627-628 (1980)

Scaling parameter

Parameter name	Parameter description	Chosen parameter values
n	n is the number of processes in the ring	5, 10, 15, 20, 25, 30, 35, 40, 45, 50

Size of the model

Parameter	Number of places	Number of transitions	Number of arcs
5	124	111	340
10	260	236	721
15	330	296	906
20	530	485	1 479
25	600	545	1 664
30	670	605	1 849
35	998	922	2 806
40	1 068	982	2 991
45	1 138	1 042	3 176
50	1 208	1 102	3 361

Structural properties

ordinary — all arcs have multiplicity one	yes
simple free choice — all transitions sharing a common input place have no other input place	no ^(a)
extended free choice — all transitions sharing a common input place have the same input places	no ^(b)
state machine — every transition has exactly one input place and exactly one output place	no ^(c)
marked graph — every place has exactly one input transition and exactly one output transition	no ^(d)
connected — there is an undirected path between every two nodes (places or transitions)	yes ^(e)
strongly connected — there is a directed path between every two nodes (places or transitions)	no ^(f)
source place(s) — one or more places have no input transitions	yes ^(g)
sink place(s) — one or more places have no output transitions	yes ^(h)
source transition(s) — one or more transitions have no input places	no ⁽ⁱ⁾
sink transitions(s) — one or more transitions have no output places	no ^(j)
loop-free — no transition has an input place that is also an output place	yes ^(k)
conservative — for each transition, the number of input arcs equals the number of output arcs	no ^(l)
subconservative — for each transition, the number of input arcs equals or exceeds the number of output arcs	no ^(m)
nested units — places are structured into hierarchically nested sequential units ⁽ⁿ⁾	no

Behavioural properties

safe — in every reachable marking, there is no more than one token on a place	? ^(o)
dead place(s) — one or more places have no token in any reachable marking	no
dead transition(s) — one or more transitions cannot fire from any reachable marking	no
deadlock — there exists a reachable marking from which no transition can be fired	yes ^(p)
reversible — from every reachable marking, there is a transition path going back to the initial marking	no ^(q)
live — for every transition t , from every reachable marking, one can reach a marking in which t can fire	no ^(r)

^(a) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(b) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(c) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(d) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(e) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(f) from place “init1” one cannot reach place “init2”.

^(g) at least place “init1”; confirmed by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(h) at least place “notelected”; confirmed by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

⁽ⁱ⁾ stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(j) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(k) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(l) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

^(m) stated by [CÆSAR.BDD](#) version 3.5 on all 10 instances (5, 10, 15, 20, 25, 30, 35, 40, 45, 50).

⁽ⁿ⁾ the definition of Nested-Unit Petri Nets (NUPN) is available from <http://mcc.lip6.fr/nupn.php>

^(o) stated by [CÆSAR.BDD](#) version 3.5 to be false on 4 instance(s) out of 10, and unknown on the remaining 6 instance(s).

^(p) Stated by PROD on March 2021.

^(q) By construction, since the model ends.

^(r) Stated by PROD on March 2021.

Size of the marking graphs

Parameter	Number of reach- able markings	Number of tran- sition firings	Max. number of tokens per place	Max. number of tokens per marking
5	$\geq 6.17794e+06$ ^(s)	?	?	≥ 15
10	$\geq 6.96577e+12$ ^(t)	?	?	≥ 30
15	$\geq 2.93539e+18$ ^(u)	?	?	≥ 45
20	$\geq 1.20319e+20$ ^(v)	?	?	≥ 60
25	?	?	?	≥ 75
30	?	?	?	≥ 90
35	?	?	?	≥ 105
40	?	?	?	≥ 120
45	?	?	?	≥ 135
50	?	?	?	≥ 150

^(s) stated by [CÆSAR.BDD](#) version 3.5.

^(t) stated by [CÆSAR.BDD](#) version 3.5.

^(u) stated by [CÆSAR.BDD](#) version 3.5.

^(v) stated by [CÆSAR.BDD](#) version 3.5.