


This form is a summary description of the model entitled "HouseConstruction" proposed for the Model Checking Contest @ Petri Nets. Models can be given in several instances parameterized by scaling parameters. Colored nets can be accompanied by one or many equivalent, unfolded P/T nets. Models are given together with property files (possibly, one per model instance) giving a set of properties to be checked on the model.

## Description

This model has been extracted from the [petriweb.org](http://www.petriweb.org) repository available at <http://www.petriweb.org>. According to the provided information, the net was designed by J. L. Peterson, from a PERT chart by F. Levy. The PERT chart contains timing information, which is not accurately translated.

The six largest instances have been added in 2019.



Graphical representation for  $N = 2$

## References

This model was probably described in: Peterson, James Lyle (1981). *Petri Net Theory and the Modeling of Systems*. Prentice Hall. ISBN 0-13-661983-5. However, this was not checked, the book being unavailable in our library.

## Scaling parameter

Parameter name	Parameter description	Chosen parameter values
$N$	initial number of tokens on place p2	2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, 32000

## Size of the model

Although the model is parameterized, its size does not depend on parameter values.

number of places: 26  
 number of transitions: 18  
 number of arcs: 51

## Structural properties

**ordinary** — *all arcs have multiplicity one* ..... yes <sup>(a)</sup>  
**simple free choice** — *all transitions sharing a common input place have no other input place* ..... yes <sup>(a)</sup>  
**extended free choice** — *all transitions sharing a common input place have the same input places* ..... yes <sup>(b)</sup>  
**state machine** — *every transition has exactly one input place and exactly one output place* ..... no <sup>(c)</sup>  
**marked graph** — *every place has exactly one input transition and exactly one output transition* ..... no <sup>(d)</sup>  
**connected** — *there is an undirected path between every two nodes (places or transitions)* ..... yes <sup>(e)</sup>  
**strongly connected** — *there is a directed path between every two nodes (places or transitions)* ..... no <sup>(f)</sup>  
**source place(s)** — *one or more places have no input transitions* ..... yes <sup>(g)</sup>  
**sink place(s)** — *one or more places have no output transitions* ..... no <sup>(h)</sup>  
**source transition(s)** — *one or more transitions have no input places* ..... no <sup>(i)</sup>  
**sink transitions(s)** — *one or more transitions have no output places* ..... yes <sup>(j)</sup>  
**loop-free** — *no transition has an input place that is also an output place* ..... yes <sup>(k)</sup>  
**conservative** — *for each transition, the number of input arcs equals the number of output arcs* ..... no <sup>(l)</sup>  
**subconservative** — *for each transition, the number of input arcs equals or exceeds the number of output arcs* ..... no <sup>(m)</sup>  
**nested units** — *places are structured into hierarchically nested sequential units* <sup>(n)</sup> ..... no

<sup>(a)</sup> stated by [CÆSAR.BDD](#) version 2.8 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(b)</sup> stated by [CÆSAR.BDD](#) version 2.8 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(c)</sup> 11 transitions are not of a state machine, e.g., transition “t3”.

<sup>(d)</sup> place “p1” is not of a marked graph.

<sup>(e)</sup> stated by [CÆSAR.BDD](#) version 2.8 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(f)</sup> from place “p2” one cannot reach place “p1”.

<sup>(g)</sup> place “p1” is a source place.

<sup>(h)</sup> stated by [CÆSAR.BDD](#) version 2.8 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(i)</sup> stated by [CÆSAR.BDD](#) version 2.8 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(j)</sup> transition “t18” is a sink transition.

<sup>(k)</sup> stated by [CÆSAR.BDD](#) version 2.8 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(l)</sup> 11 transitions are not conservative, e.g., transition “t3”.

<sup>(m)</sup> 5 transitions are not subconservative, e.g., transition “t3”.

<sup>(n)</sup> the definition of Nested-Unit Petri Nets (NUPN) is available from <http://mcc.lip6.fr/nupn.php>

## Behavioural properties

- safe** — *in every reachable marking, there is no more than one token on a place* ..... no <sup>(o)</sup>  
**dead place(s)** — *one or more places have no token in any reachable marking* ..... no <sup>(p)</sup>  
**dead transition(s)** — *one or more transitions cannot fire from any reachable marking* ..... no <sup>(q)</sup>  
**deadlock** — *there exists a reachable marking from which no transition can be fired* ..... yes <sup>(r)</sup>  
**reversible** — *from every reachable marking, there is a transition path going back to the initial marking* ..... no  
**live** — *for every transition  $t$ , from every reachable marking, one can reach a marking in which  $t$  can fire* ..... ?

## Size of the marking graphs

Parameter	Number of reach-able markings	Number of tran-sition firings	Max. number of tokens per place	Max. number of tokens per marking
$N = 2$	1501 <sup>(s)</sup>	4780 <sup>(t)</sup>	2 <sup>(u)</sup>	12 <sup>(v)</sup>
$N = 5$	1.1880E+6 <sup>(w)</sup>	7.1911E+6 <sup>(x)</sup>	5 <sup>(y)</sup>	30 <sup>(z)</sup>
$N = 10$	1.6636E+9 <sup>(aa)</sup>	1.4808E+10 <sup>(ab)</sup>	10 <sup>(ac)</sup>	60 <sup>(ad)</sup>
$N = 20$	1.3666E+13 <sup>(ae)</sup>	1.6144E+14 <sup>(af)</sup>	20 <sup>(ag)</sup>	120 <sup>(ah)</sup>
$N = 50$	1.5682E+19 <sup>(ai)</sup>	?	50 <sup>(aj)</sup>	300 <sup>(ak)</sup>
$N = 100$	?	?	?	$\geq 100$ <sup>(al)</sup>
$N = 200$	?	?	?	$\geq 200$ <sup>(am)</sup>
$N = 500$	?	?	?	$\geq 500$ <sup>(an)</sup>
$N = 2000$	?	?	?	$\geq 2000$ <sup>(ao)</sup>
$N = 4000$	?	?	?	$\geq 4000$ <sup>(ap)</sup>
$N = 8000$	?	?	?	$\geq 8000$ <sup>(aq)</sup>
$N = 16000$	?	?	?	$\geq 16000$ <sup>(ar)</sup>
$N = 32000$	?	?	?	$\geq 32000$ <sup>(as)</sup>

<sup>(o)</sup> in the initial marking, some places have several tokens (the number of which depends on  $N$ ); confirmed [CÆSAR.BDD](#) version 2.8 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(p)</sup> stated by [CÆSAR.BDD](#) version 3.3 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(q)</sup> stated by [CÆSAR.BDD](#) version 2.8 on all 14 instances (2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 8000, 16000, and 32000).

<sup>(r)</sup> confirmed at MCC'2014 by Lola and Tapaal on 8 instances, and by GreatSPN on 4 instances.

<sup>(s)</sup> computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNXDD; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNXDD, Stratagem, and Tapaal.

<sup>(t)</sup> computed at MCC'2014 by Marcie.

<sup>(u)</sup> computed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

<sup>(v)</sup> computed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

<sup>(w)</sup> computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNXDD; exact value: 1 187 984; confirmed at MCC'2014 by GreatSPN, Marcie, PNMC, PNXDD, Stratagem, and Tapaal.

<sup>(x)</sup> computed at MCC'2014 by Marcie.

<sup>(y)</sup> computed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

<sup>(z)</sup> computed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

<sup>(aa)</sup> computed at MCC'2013 by ITS-Tools, Marcie, and PNXDD; confirmed at MCC'2014 by GreatSPN, Marcie, and PNMC.

<sup>(ab)</sup> computed at MCC'2014 by Marcie.

<sup>(ac)</sup> computed at MCC'2014 by GreatSPN, Marcie, and PNMC.

<sup>(ad)</sup> computed at MCC'2014 by GreatSPN, Marcie, and PNMC.

<sup>(ae)</sup> computed at MCC'2013 by ITS-Tools, and Marcie; confirmed at MCC'2014 by GreatSPN, Marcie, and PNMC.

<sup>(af)</sup> computed at MCC'2014 by Marcie.

<sup>(ag)</sup> computed at MCC'2014 by GreatSPN, Marcie, and PNMC.

<sup>(ah)</sup> computed at MCC'2014 by GreatSPN, Marcie, and PNMC.

<sup>(ai)</sup> computed at MCC'2014 by GreatSPN.

<sup>(aj)</sup> computed at MCC'2014 by GreatSPN.

<sup>(ak)</sup> computed at MCC'2014 by GreatSPN.

<sup>(al)</sup> lower bound given by the number of initial tokens.

<sup>(am)</sup> lower bound given by the number of initial tokens.

<sup>(an)</sup> lower bound given by the number of initial tokens.

<sup>(ao)</sup> lower bound given by the number of initial tokens.

<sup>(ap)</sup> lower bound given by the number of initial tokens.

<sup>(aq)</sup> lower bound given by the number of initial tokens.

<sup>(ar)</sup> lower bound given by the number of initial tokens.

<sup>(as)</sup> lower bound given by the number of initial tokens.