

This form is a summary description of the model entitled “RERS17pb114” proposed for the Model Checking Contest @ Petri Nets. Models can be given in several instances parameterized by scaling parameters. Colored nets can be accompanied by one or many equivalent, unfolded P/T nets. Models are given together with property files (possibly, one per model instance) giving a set of properties to be checked on the model.

Description

RERS17pb114 belongs to the parallel training problems of the RERS (Rigorous Examination of Reactive Systems) challenge in 2017^(a). This model has been elaborated to preserve some properties by construction [1] and does not represent a real problem. However, it is built from patterns making it of interest to evaluate tools.

References

- 1 B. Steffen, M. Jasper, J. Meijer, and J. van de Pol. Property-preserving generation of tailored benchmark Petri nets. In 17th International Conference on Application of Concurrency to System Design, ACSD 2017, Zaragoza, Spain, June 25–30, 2017, pages 1–8.

Scaling parameter

Parameter name	Parameter description	Chosen parameter values
N	Initial Marking Multiplier	1, 2, 3, 4, 5, 6, 7, 8, 9

Size of the model

Although the model is parameterized, its size does not depend on parameter values.

number of places: 1446
number of transitions: 151 085
number of arcs: 604 252

Structural properties

ordinary — all arcs have multiplicity one yes
simple free choice — all transitions sharing a common input place have no other input place no^(b)
extended free choice — all transitions sharing a common input place have the same input places no^(c)
state machine — every transition has exactly one input place and exactly one output place no^(d)
marked graph — every place has exactly one input transition and exactly one output transition no^(e)
connected — there is an undirected path between every two nodes (places or transitions) yes^(f)
strongly connected — there is a directed path between every two nodes (places or transitions) no^(g)
source place(s) — one or more places have no input transitions yes^(h)
sink place(s) — one or more places have no output transitions no⁽ⁱ⁾

^(a) See <http://www.rers-challenge.org/2017/>.

^(b) 302048 arcs are not simple free choice, e.g., the arc from place “p1120” (which has 272 outgoing transitions) to transition “t_102312_a51_SIGPWR” (which has 2 input places).

^(c) transitions “t_80279_a4_SIGTSTP” and “t_102312_a51_SIGPWR” share a common input place “p1120”, but only the former transition has input place “p832”.

^(d) 151025 transitions are not of a state machine, e.g., transition “t_141209_a90_SIGINFO”.

^(e) 1446 places are not of a marked graph, e.g., place “p1120”.

^(f) stated by CÆSAR.BDD version 2.8 on all 9 instances (1, 2, 3, 4, 5, 6, 7, 8, and 9).

^(g) from place “p730” one cannot reach place “p1247”.

^(h) there exist 18 source places, e.g., place “p1247”.

⁽ⁱ⁾ stated by CÆSAR.BDD version 2.8 on all 9 instances (1, 2, 3, 4, 5, 6, 7, 8, and 9).

- source transition(s)** — one or more transitions have no input places no ^(j)
- sink transitions(s)** — one or more transitions have no output places no ^(k)
- loop-free** — no transition has an input place that is also an output place no ^(l)
- conservative** — for each transition, the number of input arcs equals the number of output arcs yes ^(m)
- subconservative** — for each transition, the number of input arcs equals or exceeds the number of output arcs yes ⁽ⁿ⁾
- nested units** — places are structured into hierarchically nested sequential units ^(o) ? ^(p)

Behavioural properties

- safe** — in every reachable marking, there is no more than one token on a place ? ^(q)
- dead place(s)** — one or more places have no token in any reachable marking ?
- dead transition(s)** — one or more transitions cannot fire from any reachable marking ?
- deadlock** — there exists a reachable marking from which no transition can be fired ?
- reversible** — from every reachable marking, there is a transition path going back to the initial marking ?
- live** — for every transition t , from every reachable marking, one can reach a marking in which t can fire ?

Size of the marking graphs

Parameter	Number of reachable markings	Number of transition firings	Max. number of tokens per place	Max. number of tokens per marking
$n = 1$	$\geq 3.70739e+06$ ^(r)	?	1 ^(s)	18 ^(t)
$n = 2$?	?	?	36 ^(u)
$n = 3$?	?	?	54 ^(v)
$n = 4$?	?	?	72 ^(w)
$n = 5$?	?	?	90 ^(x)
$n = 6$?	?	?	108 ^(y)
$n = 7$?	?	?	126 ^(z)
$n = 8$?	?	?	144 ^(aa)
$n = 9$?	?	?	162 ^(ab)

(j) stated by [CÆSAR.BDD](#) version 2.8 on all 9 instances (1, 2, 3, 4, 5, 6, 7, 8, and 9).
 (k) stated by [CÆSAR.BDD](#) version 2.8 on all 9 instances (1, 2, 3, 4, 5, 6, 7, 8, and 9).
 (l) 68736 transitions are not loop free, e.g., transition “t_141229_a90_SIGINFO”.
 (m) stated by [CÆSAR.BDD](#) version 2.8 on all 9 instances (1, 2, 3, 4, 5, 6, 7, 8, and 9).
 (n) stated by [CÆSAR.BDD](#) version 2.8 on all 9 instances (1, 2, 3, 4, 5, 6, 7, 8, and 9).
 (o) the definition of Nested-Unit Petri Nets (NUPN) is available from <http://mcc.lip6.fr/nupn.php>
 (p) yes for $N = 1$ (the unit-safeness property only holds for $N = 1$) and no otherwise.
 (q) The net is structurally safe when $N = 1$, otherwise it is not; confirmed by [CÆSAR.BDD](#) version 2.8.
 (r) stated by [CÆSAR.BDD](#) version 3.3.
 (s) stated by [PNML2NUPN](#) 3.1.0.
 (t) number of initial tokens, because the net is conservative.
 (u) number of initial tokens, because the net is conservative.
 (v) number of initial tokens, because the net is conservative.
 (w) number of initial tokens, because the net is conservative.
 (x) number of initial tokens, because the net is conservative.
 (y) number of initial tokens, because the net is conservative.
 (z) number of initial tokens, because the net is conservative.
 (aa) number of initial tokens, because the net is conservative.
 (ab) number of initial tokens, because the net is conservative.