

Size of the derived P/T model instances

Parameter	Number of places	Number of transitions	Number of arcs
$N = 2$	438	357	1998
$N = 3$	972	1016	5840
$N = 4$	1830	2340	13565
$N = 5$	3090	4674	27162
$N = 6$	4830	8435	49028
$N = 7$	7128	14112	81968
$N = 8$	10062	22266	129195

Structural properties

ordinary — all arcs have multiplicity one	✓
simple free choice — all transitions sharing a common input place have no other input place	✗ (a)
extended free choice — all transitions sharing a common input place have the same input places	✗ (b)
state machine — every transition has exactly one input place and exactly one output place	✗ (c)
marked graph — every place has exactly one input transition and exactly one output transition	✗ (d)
connected — there is an undirected path between every two nodes (places or transitions)	✗ (e)
strongly connected — there is a directed path between every two nodes (places or transitions)	✗ (f)
source place(s) — one or more places have no input transitions	✓ (g)
sink place(s) — one or more places have no output transitions	✓ (h)
source transition(s) — one or more transitions have no input places	✗ (i)
sink transitions(s) — one or more transitions have no output places	✗ (j)
loop-free — no transition has an input place that is also an output place	✗ (k)
conservative — for each transition, the number of input arcs equals the number of output arcs	✗ (l)
subconservative — for each transition, the number of input arcs equals or exceeds the number of output arcs	✗ (m)
nested units — places are structured into hierarchically nested sequential units ⁽ⁿ⁾	✗

Behavioural properties

safe — in every reachable marking, there is no more than one token on a place	✓ (o)
deadlock — there exists a reachable marking from which no transition can be fired	✓ (p)
reversible — from every reachable marking, there is a transition path going back to the initial marking	✗ (q)
quasi-live — for every transition t , there exists a reachable marking in which t can fire	✗ (r)
live — for every transition t , from every reachable marking, one can reach a marking in which t can fire	✗ (s)

(a) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(b) stated by [CÆSAR.BDD](#) version 2.6 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(c) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(d) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(e) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(f) the net is not connected and, thus, not strongly connected.

(g) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(h) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(i) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(j) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(k) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(l) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(m) stated by [CÆSAR.BDD](#) version 1.7 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(n) the definition of Nested-Unit Petri Nets (NUPN) is available from <http://mcc.lip6.fr/nupn.php>

(o) stated by [CÆSAR.BDD](#) version 2.0 to be true on 2 instance(s) out of 7, and unknown on the remaining 7 instance(s).

(p) stated by [CÆSAR.BDD](#) version 2.0 to be true on 2 instance(s) out of 7, and unknown on the remaining 7 instance(s); confirmed at MCC'2014 by Helena on all colored instances, and by Lola and Tapaal on (almost) all P/T instances.

(q) the marking graph has deadlocks and contains more than one reachable marking.

(r) stated by [CÆSAR.BDD](#) version 2.0 on all 7 instances (2, 3, 4, 5, 6, 7, and 8).

(s) the net is not quasi-live and, thus, not live.

Size of the marking graphs

Parameter	Number of reachable markings	Number of transition firings	Max. number of tokens per place	Max. number of tokens per marking
$N = 2$	241 ^(t)	448 ^(u)	1 ^(v)	14 ^(w)
$N = 3$	974 325 ^(x)	3.5991E+6 ^(y)	1 ^(z)	30 ^(aa)
$N = 4$	2.9191E+11 ^(ab)	?	1 ^(ac)	52 ^(ad)
$N = 5$	6.3570E+18 ^(ae)	?	?	≥ 60
$N = 6$?	?	?	≥ 84
$N = 7$?	?	?	≥ 112
$N = 8$?	?	?	≥ 144

Other properties

When analyzing the unfolded place-transition nets, the [CÆSAR.BDD](#) tool found a high number of source places, of sink places, of places that never get a token in any reachable marking, and of transitions that are not quasi-live. This is due to the particular tool that has been used to produce these unfolded nets.

^(t) computed at MCC'2013 by Alpina, ITS-Tools, Marcie, Neco, and PNXDD; confirmed by [CÆSAR.BDD](#) 1.8; confirmed at MCC'2014 by Helena on the colored net instance, and by GreatSPN, Marcie, PNMC, PNXDD; Stratagem, and Tapaal on the P/T net instance.

^(u) computed at MCC'2014 by Helena on the colored net instance, and by Marcie on the P/T net instance.

^(v) computed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

^(w) computed at MCC'2014 by GreatSPN, Marcie, PNMC, and Tapaal.

^(x) computed at MCC'2013 by Alpina, ITS-Tools, Marcie, and PNXDD; confirmed by [CÆSAR.BDD](#) 1.8; confirmed at MCC'2014 by Helena on the colored net instance, and by GreatSPN, Marcie, PNMC, and PNXDD on the P/T net instance.

^(y) computed at MCC'2014 by Helena on the colored net instance, and by Marcie on the P/T net instance.

^(z) computed at MCC'2014 by GreatSPN, Marcie, and PNMC.

^(aa) computed at MCC'2014 by GreatSPN, Marcie, and PNMC.

^(ab) computed at MCC'2013 by GreatSPN, ITS-Tools, and PNXDD; confirmed at MCC'2014 by PNMC and PNXDD.

^(ac) computed at MCC'2014 by PNMC.

^(ad) computed at MCC'2014 by PNMC.

^(ae) computed at MCC'2014 by PNMC.